

# 409KT/KM80X

CONSTRUCTION VEHICLE   
SEATS



BACKREST  
ADJUSTMENT

HEATER

SWIVEL  
HANDLE

FORE AND AFT  
ADJUSTMENT

WEIGHT  
ADJUSTMENT

HEIGHT  
ADJUSTMENT

# 409KT/KM80X

### 409KT / KM80X

Air suspension	N/A
Air suspension with 12V or 24V built-in compressor	▲
Mechanical suspension	●
Weight adjustment	Manual up to 150 kgs.
Suspension stroke	80 mm
Height adjustment	60 mm
Turn Table	▲
Slide travel	100 mm
Lumbar adjustment	N/A
Adjustable / Foldable armrests	N/A
Adjustable headrest	▲
Backrest adjustment	●
Vinyl trim (Cut&Sew)	●
Cloth trim (Cut&Sew)	▲
Genuine leather trim	▲
3-point seat belt	N/A
2-point seat belt	▲
Document box-pouch	N/A
Heater	▲
Operator presence switch	▲
Slides between seat top and suspension	●
Standard connection widths	120 mm and 140 mm
Testing	ISO 6683 - ISO 7096- EM2,EM3,EM4,EM5,EM6,EM8,EM9 - ECE R16.08 - ISO 3795

