

# P1408/M61X

CONSTRUCTION VEHICLE   
SEATS



# P1408/M61X

P1408/M61X	
Air suspension	N/A
Air suspension with 12V or 24V built-in compressor	▲
Mechanical suspension	●
Weight adjustment	Manual up to 150 kgs.
Suspension stroke	60 mm
Height adjustment	60 mm
Turn Table	▲
Slide travel	190 mm
Lumbar adjustment	▲
Adjustable / Foldable armrests	▲
Adjustable headrest	●
Backrest adjustment	●
Seat cushion tilt adjustment	▲ Order P1410/M61X
Seat cushion depth adjustment	▲ Order P1410/M61X
Vinyl trim (Cut&Sew)	●
Cloth trim (Cut&Sew)	▲
Genuine leather trim	▲
3-point seat belt	▲
2-point seat belt	▲
Document box-pouch	▲
Front Controls (except backrest recline handle)	●
LH Controls	N/A
RH Controls	N/A
Heater	▲
Operator presence switch	▲
Slides between seat top and suspension	●
Standard connection widths	260 mm
Optional connection widths	280 mm - 320 mm
Testing	EU 1322/2014 Annex XIV - Class I, II, III - ISO 6683 - ECE R16.08 - ISO 3795

