

P160/M110X

CONSTRUCTION VEHICLE 
SEATS



P160/M110X

P160/M110X	
Air suspension	N/A
Air suspension with 12V or 24V built-in compressor	▲
Mechanical suspension	●
Weight adjustment	Manual up to 150 kgs.
Suspension stroke	80 mm
Height adjustment	60 mm
Turn Table	▲
Adjustable shock absorber	N/A
Slide travel	190 mm
Lumbar adjustment	▲
Horizontal isolator	N/A
Adjustable / Foldable armrests	▲
Adjustable headrest	●
Backrest adjustment	●
Seat cushion tilt adjustment	▲ Order P170/M110X
Seat cushion depth adjustment	▲ Order P170/M110X
Vinyl trim (Cut&Sew)	▲
Cloth trim (Cut&Sew)	▲ Order P165/M110X
Vinyl trim (Vacuum type)	●
Cloth trim (Vacuum type)	▲
3-point seat belt	N/A
2-point seat belt	▲
Document box-pouch	▲
Front Controls (except backrest recline handle)	●
LH Controls	N/A
RH Controls	N/A
Heater	▲
Operator presence switch	▲
Slides between seat top and suspension	●
Standard connection widths	260 mm
Optional connection widths	280mm (Order ----/CM110X)
Testing	EU 1322/2014 Annex XIV - Class I, II, III - ISO 6683 - ISO 7096 - EM3,EM5,EM6 - ECE R16.08 - ISO 3795

