

P215/CEA150D

CONSTRUCTION VEHICLE 
SEATS



P215/CEA150D

P215/CEA150D	
Air suspension	N/A
Air suspension with 12V or 24V built-in compressor	●
Mechanical suspension	▲
Weight adjustment	Automatic up to 150kgs.
Suspension stroke	140 mm
Height adjustment	80 mm
Turn Table	▲
Adjustable shock absorber	▲
Slide travel	190mm
Lumbar adjustment	▲
Horizontal isolator	●
Adjustable / Foldable armrests	▲
Adjustable headrest	●
Backrest adjustment	●
Seat cushion tilt adjustment	●
Seat cushion depth adjustment	●
Vinyl trim (Cut&Sew)	▲
Cloth trim (Cut&Sew)	●
Vinyl trim (Vacuum type)	N/A
Cloth trim (Vacuum type)	N/A
3-point seat belt	▲
2-point seat belt	▲
Document box-pouch	▲
Front Controls (except backrest recline handle)	●
LH Controls	N/A
RH Controls	N/A
Heater	▲
Operator presence switch	▲
Slides between seat top and suspension	●
Standard connection widths	280mm
Optional connection widths	260mm (Order ----/EA150D)
Testing	ISO 6683 - ISO 7096-EM3,4,6 - ECE R16.08 - ISO 3795

