

# TP1101/M80H3

RAILWAY SEATS



# TP1101/M80H3

| TP1101/M80H3                                       |  |
|--|--|
| Air suspension                                     | ▲  |
| Air suspension with 12V or 24V built-in compressor | ▲  |
| Mechanical suspension                              | ●  |
| Weight adjustment                                  | Manual up to 150kgs.                       |
| Suspension stroke                                  | 80mm                                       |
| Height adjustment                                  | 60mm                                       |
| Optional suspension stroke                         | 60 mm - 100 mm                             |
| Turn Table   | ●  |
| Adjustable shock absorber                          | N/A  |
| Slide travel                                       | 190mm                                      |
| Lumbar adjustment                                  | ●  |
| Adjustable armrests                                | ▲  |
| Adjustable headrest                                | ●  |
| Backrest adjustment                                | ●  |
| Seat cushion tilt adjustment                       | ●  |
| Seat cushion depth adjustment                      | ●  |
| Pedestal height adjustment                         | 120mm                                      |
| Vinyl trim   | N/A  |
| Cloth trim   | ●  |
| Genuine leather trim                               | N/A  |
| 3-point seat belt                                  | ▲  |
| 2-point seat belt                                  | ▲  |
| Document box-pouch                                 | ▲  |
| Front Controls                                     | N/A  |
| LH Controls  | ●  |
| RH Controls  | ▲  |
| Heater   | ▲  |
| Operator presence switch                           | ▲  |
| Slides between seat top and suspension             | N/A  |
| Standard connection widths                         | 216mm                                      |
| Optional connection widths                         | 230 - 260 - 280 - 320 - 328mm              |
| Testing  | EN 15085-2 CL2<br>EN 45545-2<br>2002/44/CE |

